

Compact and lightweight LCD laser projector

PT-VMZ61



KEY FEATURES

- Compact and lightweight LCD laser projector
- Clear Images That Are Easy to See in Bright Rooms
- Installation Flexibility Adapts Projection to Any Space
- Smooth and Effortless Collaboration

Product Specifications

SPECIFICATIONS

Projector type	LCD projectors
LCD Panel Panel Size	16.3 mm (0.64 in) diagonal (16:10 aspect ratio)
LCD Panel Display System	Transparent LCD panel (x 3, R/G/B)
LCD Panel Drive Method	Active matrix
LCD Panel Pixels	2,304,000 (1920 x 1200) pixels
Light Source	Laser diode
Light Output*1 *2	6,200 lm
Time until light output declines to 50 %*3	20,000 hours (NORMAL/QUIET)/24,000 hours (ECO)
Resolution	WUXGA (1920 x 1200 pixels)
Contrast Ratio*1	3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].)

Screen Size (Diagonal)	0.76–7.62 m (30–300 in), 16:10 aspect ratio
Center-to-corner zone ratio*1	85 %
Lens	1.6x manual zoom (throw ratio: 1.09–1.77:1), manual focus lens, F 1.60–2.12, f 15.30–24.64 mm
Lens shift Vertical (from center of screen)	+44 %, 0 % (manual)
Lens shift Horizontal (from center of screen)	+20 %, -20 % (manual)
Keystone Correction Range	Vertical: ±25 °, Horizontal: ±35 °
Installation	Ceiling/floor, front/rear, free 360-degree installation
Terminals HDMI In	HDMI 19-pin x 2 (Compatible with HDCP, Deep Color, 4K/30p*4 signal input), CEC supported
Terminals Computer 1 In	D-sub 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals Computer 2 In	D-sub 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals AUDIO 1/2 IN	M3 stereo mini-jack x 2
Terminals Variable Audio Out	M3 stereo mini-jack x 1
Terminals Serial In	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)
Terminals DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control)(HDBaseT™ compliant), 100Base-TX (Compatible with PjLink™ [Class 2]),HDCP, Deep Color, 4K/30p*4 signal input)
Terminals LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PjLink™ [Class 2]
Terminals USB(VIEWER/WIRELESS/DC OUT)	USB connector (Type A) x 1 for Memory Viewer function, optional Wireless Module AJ-WM50 Series, power supply (DC 5 V, maximum 2 A*5)
Power Supply	AC 100 V–240 V, 50/60 Hz
Power Consumption	370 W(TBD)
Built in Speaker	10 W monaural
Cabinet Materials	Molded plastic
Filter*6	Included (Estimated maintenance time: approx. 20,000 hours)
Operation noise*1	39 dB (NORMAL/ECO), 29 dB (QUIET)
Dimensions (W x H x D)	399 mm x 115 mm x 348 mm (15 23/32" x 4 17/32" x 13 11/16") (not including protruding parts)399 mm x 133 mm x 348 mm (15 23/32" x 5 1/4" x 13 11/16") (with feet at shortest position)
Weight with supplied lens*7	Approx. 6.9 kg (15.21 lbs)
Operating Environment	Operating temperature: 0–45 °C (32–113 °F)*8*9, Operating humidity: 20–80 % (no condensation)
Applicable Software	Multi Monitoring & Control Software, Logo Transfer Software, Presenter Light Software for Windows®*10, Wireless Projector App for iOS/Android™*11
Note	Note: Availability varies by country or region.*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 When [PICTURE MODE] is set to [DYNAMIC], [LIGHT POWER] is set to [NORMAL], [DAYLIGHT VIEW] is set to [OFF],and [AUTO POWER SAVE] is set to [OFF]. *3 Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m3 of particulatematter). Estimated time until light output declines to 50 % varies depending on environment. *4 4K signals are converted to the projector's resolution upon projection. *5 On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready. *6 Filter cleaningcycle varies depending on environment. Filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m3), 10,000 hours (under dust conditions of 0.15 mg/m3). *7 Average value. May differ depending on the actual unit. *8 Lightoutput is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level. *9 When optional AJ-WM50 Series wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F).*10 When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy, while images and sound are being transmitted. *11 Whenusing the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).

URL: <https://business.panasonic.co.uk/visual-system/pt-vmz61>

CONTACT

Web: <https://business.panasonic.co.uk/visual-system/contact-us>