

Key Features

Bright Images in Any Environment | Fit For Classrooms of All Sizes | Interactive module compatible | Instant Activation Upon Signal Detection | SuperColor™: Best in Class Color Accuracy



Product Description

The PS500X is a high brightness XGA short throw projector for education. With the ability to project 77" images from a distance of 0.95m from any projection surface, the projector is flexible enough to fit any classroom design and keeps the presenter clear of the projection beam. For times when lights in the classroom must be kept on, a high brightness of 3,500 ANSI Lumens ensures that images remain clear and detailed. ViewSonic exclusive SuperColor™ technology offers a true-to-life color accuracy for projected images. The energy-saving SuperEco mode reduces power consumption and extends lamp life to a lengthy 15,000 hours. In addition, PS500X is compatible with the optional PJ-vTouch-10S interactive module, which allows you to use a stylus or finger touch to annotate on projected images – turning class into an engaging interactive teaching environment.

Visit Us ■ www.viewsonic.com

SPECIFICATION

Projection System:	0.55" XGA
Native Resolution:	1024x768
DC Type:	DC3
Brightness:	3500
Contrast Ratio with SuperEco Mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light Source Life (Nor/SuperEco):	5000/15000
Lamp Watt:	190W
Lens:	F=2.6, f=6.9mm
Projection Offset:	130%+/-5%
Throw Ratio:	0.61
Image Size:	60" - 300"
Throw Distance:	0.74m-2.23m (77" @ 0.95m)
Keystone:	+/- 40° (Vertical)
Optical Zoom:	Fixed
Audible Noise (Eco):	27dB
Response Time:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Horizontal Frequency:	15K~102KHz(TBD)
Vertical Scan Rate:	48~120Hz
Interactive Camera:	Optional (vTouch-10s)

INPUT

Computer in (share with component):	2
Audio-in (3.5mm):	1

OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W

CONTROL

RS232:	1
USB Type Mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260WStandby: <0.5W
Operating Temperature:	0~40°C
Net Weight:	2.6kg
Dimensions (WxDxH) with Adjustment Foot:	292x236x115mm

Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
-----------	--

STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	1
Lens Cover:	1

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-108
--------------------	---------