

Key Features

- Energy-efficient SmartEco+ Mode
- Vertical Lens Shift
- vColorTuner
- · Customised User Modes
- Dual HDMI inputs and USB power supply



Product **Description**

The ViewSonic CPB701HD is a high brightness 3,700 ANSI lumens projector featuring a Full HD 1080p resolution that offers impressive visual performance in a brightly lit living room or meeting room. The projector adopts the latest lamp design to extend lamp life up to 20,000 hours under SuperEco+ mode, effectively reducing lamp replacement and maintenance costs. A digital lens shift allows users to make adjustments by remote control, and it's also compatible with the vColorTuner function for colour profile exchange and adjustments. The dual HDMI inputs and USB power supply allow users to connect to a multitude of multimedia devices for gaming, movies, or a wireless dongle for wireless presentation.



07 08 09 10 11 12 13

- 1. Keypad
- 2. LED indicator
- 3. Power Key
- 4. Zoom/Focus
- 5. Front IR
- 6. Projection Lens
- 7. Audio in/out

- 8. Dual HDMI
- 9. USB Type A
- 10. Computer in
- 11. Monitor out
- 12. RS232
- 13. Kensington® Lock Slot

SPECIFICATION	
Native Resolution:	1920x1080
Brightness:	3700 ANSI Lumens
Contrast Ratio with SuperEco Mode:	20000:1
Display Colour:	1.07 Billion Colours
Light Source Type:	Lamp
Light Source Life (Normal):	6000
Light Source Life (SuperEco):	20000
Lamp Watt:	203W
Lens:	F=2.0~2.05,f=15.843mm~17.445mm
Projection Offset:	110%+/-6%
Throw Ratio:	1.5-1.65
Image Size:	30" - 300"
Throw Distance:	1m~10.96m (100"@3.32m)
Keystone:	+/- 40° (V)
Lens Shift V. Range:	Yes (+/- 5%)
Optical Zoom:	1.1x
Digital Zoom:	0.8x ~ 2.0x
Audible Noise (Normal):	31dB
Audible Noise (Eco):	27dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz
INPUT	
Computer in (share with component):	1
Audio-in (3.5mm):	1
HDMI:	2 (HDMI 1.4/ HDCP 1.4)
ОUТРUТ	
Monitor out:	1
Audio out (3.5mm):	1
Speaker:	10W
USB Type A (Power):	1 (5V/1.5A)
CONTROL	

RS232 (DB 9-pin male):

OTHERS

Lamp/Light Source:

OTHERS	
Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 300W Standby: <0.5W
Operating Temperature:	0~35℃
Net Weight:	2.59kg
Dimensions (WxDxH) with Adjustment Foot:	312x222x108mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S- Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
STANDARD ACCESSORY	
Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	1
OPTIONAL ACCESSORY	

RLC-119

 $\label{thm:copyright} \ @\ ViewSonic\ Corporation\ 2000-2024.\ All\ rights\ reserved.$